



RENOVATION PLASTER



DESCRIPTION

Plaster in powder for fine coats, covering artex, levelling and filling cracks and small fissures

ADVANTAGES

- ✓ Good breathability.
- ✓ Extraordinary adherence to textured surfaces, artex, etc.
- ✓ Can be applied in thick coats with minimum waste.
- ✓ Easy to prepare and apply with a trowel or float.
- ✓ Fine, hard wearing quality finish for any type of decoration.
- ✓ Quick-drying.

RECOMMENDED USES

Ideal for plastering interior walls, textured and artex finishes and for levelling after removing wallpaper, etc.

PRESENTATION

Colour: White.
5 kg and 15 kg sacks.

TECHNICAL CHARACTERISTICS

Composition: Water-soluble polymers and mineral content.

Paste density: 1.65Kg./L.

Coverage: 1Kg/ m² and mm thick.

Drying: 10 hours per coat depending on thickness.

Working time: 3 to 4 hours depending on absorption and temperature.

APPLICATION

Coats: 1 or more as necessary.

Dilution: One part water to two and a half parts product.

Application temperature: 5 to 30 °C.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be filled and levelled. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer.

STORAGE

Keep away from temperatures below 5 °C. and damp.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com